

Coaxial Paint & Air Hose

The Exitflex low pressure coaxial paint spray hose kit comprises an anodised aluminium Y-block assembly and integrated swivel with stainless steel fittings connected to an anti-static rubber air hose with a separate PA12 nylon material delivery tube located within the air line.



- Supremely flexible, ultra-light and highly manoeuvrable allowing easier access into awkward sections and minimal operator fatigue reducing RSI injury.
- Specially designed lightweight aluminium connecting Y-block to accommodate the combined air and fluid hose.
- Fluid tube located inside air hose, creating a compact and tidy assembly.
- Anti-Static rubber air line with 20 bar maximum working pressure.
- PA12 nylon fluid tube.
- Optional PTFE tubing available if required for more sensitive materials and easier flushing.

PART NO.		Inner Diameter		Outer Diameter		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
		inch	mm	inch	mm	Psi	BAR	Psi	BAR	inch	mm
CAF6.16	LCC-16	3/8"	9	5/8"	16	290	20	870	60	3"	75
	PA12 ENF6/4	5/32"	4	15/64"	6	348	24	800	55		

Exitflex (UK) Limited

3 Airfield Road, Airfield Industrial Estate, Christchurch, Dorset BH23 3TG

T: +44 (0)1202 478334 **F:** +44 (0)1202 488110 **E:** sales@exitflex.co.uk

www.exitflex.co.uk